REPORT DOCUMENTATION PAGE	Form Approved OMB NO. 0704-0188

Public Reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comment regarding this burden estimates or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188,) Washington, DC 20503.

1. AGENCY USE ONLY (Leave Blank)	2. REPORT DATE 7/1/2004	3. REPORT TYPE AND DATES COVERED Final Progress Report, 8/7/2000 – 12/31/2003
4. TITLE AND SUBTITLE Defects in Ion-Implanted Silicon Carbide.		5. FUNDING NUMBERS DAAD19-00-1-0490
6. AUTHOR(S) Mulpuri V.Rao		
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) George Mason University, Fairfax, Va 22030.		8. PERFORMING ORGANIZATION REPORT NUMBER ARCHIVE
9. SPONSORING / MONITORING AGENCY NAME(S) AND ADDRESS(ES) U. S. Army Research Office P.O. Box 12211 Research Triangle Park, NC 27709-2211		**20040713 017** 41080.5-MS

11. SUPPLEMENTARY NOTES
The views, opinions and/or findings contained in this report are those of the author(s) and should not be construed as an official Department of the Army position, policy or decision, unless so designated by other documentation.

12 a. DISTRIBUTION / AVAILABILITY STATEMENT Approved for public release; distribution unlimited.	12 b. DISTRIBUTION CODE

13. ABSTRACT (Maximum 200 words)

Defects that introduce electrically active deep levels in ion-implanted Silicon Carbide (SiC) were studied by performing capacitance Deep- Level Transient- Spectroscopy (DLTS) and transconductance frequency dispersion measurements on fully implanted MESFETs in bulk semi-insulating 4-H SiC, MISFETs in 6-H SiC and double implanted p-n and n-p junction diodes in 4-H SiC. The junction diodes made with aluminum and phosphorus implantations exhibited higher reverse leakage current compared to those made by nitrogen and boron implantations. In all samples implanted with nitrogen a defect complex involving nitrogen and a point defect (introduced by the ion-implantation process) is observed with a trap level introduced at 0.51 eV above the valence band. Phosphorus implant-native defect related peaks are observed at 0.6 and 0.7 eV above the valence band. In all boron implanted samples, a prominent electrically active boron related D-center defect is seen at 0.62 eV above the valence band. In aluminum implanted samples an intrinsic vacancy related defect is seen at 0.78 eV above the valence band. Surface state related defects were observed in the N-implanted channel region at energies 0.18 eV, 0.3 eV and 0.4 eV. Several defects were observed in the gate insulator and insulator/channel interface.

14. SUBJECT TERMS Defects, Deep-Levels, Silicon Carbide (SiC), DLTS, transconductance frequency dispersion.			15. NUMBER OF PAGES 6
			16. PRICE CODE

17. SECURITY CLASSIFICATION OR REPORT UNCLASSIFIED	18. SECURITY CLASSIFICATION ON THIS PAGE UNCLASSIFIED	19. SECURITY CLASSIFICATION OF ABSTRACT UNCLASSIFIED	20. LIMITATION OF ABSTRACT UL

Project Title: Defects in ion-implanted Silicon Carbide
Grant Fund Code: DAAD19-00-1-0490
Principle Investigators: Mulpuri V. Rao and D. Ioannou
Army Research Lab Collaborator: Kenneth Jones, Adelphi, Maryland.
Graduate Students Supported by the Grant:
1. Souvick Mitra (His Ph. D. thesis work was entirely supported by this ARO Grant)
2. Taizo Okayama (Masters Student)

Listing of Peer-reviewed Journal Article Publications Acknowledging the ARO Grant:

1. S. Mitra, M. V. Rao, K. Jones, N. Papanicolaou, and S. Wilson, "Deep levels in ion-implanted field-effect-transistors in SiC", Solid-State Electronics, Vol. 47 (2), Feb. 2003, pp. 193-198
2. M. V. Rao, "Maturing ion-implantation technology and its device applications in SiC", Solid-State Electronics, Vol. 47 (2), Feb. 2003, pp. 213-222.
3. S. Mitra, M. V. Rao, N. Papanicolaou, K. A. Jones, M. Derenge, O. W. Holland, R. D. Vispute, and S. R. Wilson, "Deep-level transient spectroscopy study on double implanted n^+-p and p^+-n 4H-SiC diodes", Journal of Applied Physics, Vol. 95 (1), Jan. 2004, pp. 69-75.
4. S. Mitra, M. V. Rao, and K. A. Jones, "Transconductance frequency dispersion measurements on MESFETs made on bulk semi-insulating 4H-SiC by nitrogen ion-implantations", Solid-State Electronics, Vol. 48 (1), Jan. 2004, pp. 143-147.

Statement of the Problem Studied: Ion-implantation is the only reliable technique for planar selective area doping of Silicon Carbide (SiC) devices[1]. Ion-implantation technology for both donor- and acceptor- dopants in SiC has been developed[2]. Ion-implantation has been used to create channel, source and drain regions of SiC field-effect-transistors[3-5] and p- and n-regions of p-n junctions[6]. The performance and reliability of these SiC devices remains a problem, partially due to channel/insulator, channel/substrate interface and p-n junction interface deep-level defects. In this project, deep-level defects: (a) at the interface of double implanted 4H-SiC p-n and n-p junction diodes, (b) at the interface of channel/gate insulator in n-channel 6H-SiC Metal-Insulator-Semiconductor Field-Effect-Transistors (MISFETs) and (c) at the gate/channel and channel/substrate interface of n-channel 4H-SiC MEtal-Semiconductor Fild-Effect-Transistor (MESFET) have been studied. The MISFETs were made in p-type epitaxial layers and the MESFETs in semi-insulating bulk substrates. Deep levels in the double-implanted p-n and n-p junction diodes and MISFETs were studied by capacitance Deep-Level-Transient-Spectroscopy (DLTS), where as the deep levels in MESFETs were studied by both capacitance DLTS and transconductance frequency dispersion spectroscopy.

Summary of the Most Important Results:

Devices used in this study were made by nitrogen, phosphorus, aluminum, and boron implantations, to study the defects introduced by implantations of various species[3,5,7].

In all samples implanted with nitrogen a defect complex involving nitrogen and a point defect (introduced by the ion-implantation process) is observed with a trap level introduced at 0.51 eV above the valence band[7-9]. In n^+-p junction diodes made using phosphorus implantation the defect density is very high yielding poor device performance. In the phosphorus ion-implanted samples, phosphorus implant-native defect related peaks are observed at 0.6 and 0.7 eV above the valence band[7]. In all boron implanted samples, a prominent electrically active boron related D-center defect is seen at 0.62 eV above the valence band[7]. In aluminum implanted samples an intrinsic vacancy related defect is seen at 0.78 eV above the valence band, and a background nitrogen at carbon lattice site complex defect is seen at 0.15 eV above the valence band[7]. Several unidentified defects are seen in Al implanted samples[7]. The lattice damage in Al-implanted samples is so high that the p^+-n junction diodes made using Al-implantation yielded poor device performance. The concentration of traps in p-n and n-p junction diodes made by phosphorus and aluminum implantations is very high compared to the diodes made by nitrogen and boron implantations, resulting in high junction leakage currents in the former[6,7].

In the transconductance frequency dispersion measurements performed on MESFETs made in vanadium-doped semi-insulating 4H-SiC, a vanadium deep donor is observed at 0.65 eV below the conduction band and a nitrogen dopant-defect complex at 0.52 eV[9]. The vanadium deep donor is intentionally introduced to obtain semi-insulating behavior in the bulk 4H-SiC substrate. The defect involved in the complex responsible for the 0.52 eV peak is a point defect. Three surface state related defects were observed in the N-implanted channel region at energies 0.18 eV, 0.3 eV and 0.4 eV[9]. For low concentration ($\sim 6 \times 10^{17}$ cm^{-3}) nitrogen implanted MESFET channel, the magnitude of transconductance frequency dispersion is comparable to dispersion in epitaxially grown channel layer, indicating the attractiveness of nitrogen implantation to achieve lightly doped n-type channel regions in SiC MESFETs.

Five gate dielectric traps and eight interface hole/electron traps were revealed for MISFETs. Gate dielectric traps were distinguished by different activation energies of 0.109, 0.132, 0.15, 0.4 and 0.6 eV[8]. Two shallow gate dielectric/semiconductor interface traps were identified at E_v +0.2 eV (hole trap) and E_c -0.362 eV (electron trap)[8]. Four deep level traps were found in the activation energy range of 0.6-0.8 eV above the valance band edge with capture cross-section $\sim 10^{-16}$ -10^{-17} cm^2. Other traps were detected at E = 0.437 and 0.47 eV above E_v[8]. For both MESFETs and MISFETs, effective channel mobility is much smaller than the bulk mobility due to residual implant lattice damage and/or dielectric/ SiC interface traps and channel/substrate interface traps[3-5].

BIBLIOGRAPHY:

1. R.F Davis, G. Kelner, M.Shur, J.W. Palmour, and J.A Edmond, Proc IEEE 79, 677(1991).
2. M.V.Rao Solid-State Electronics 47, 231 (2003).

3. X.W.Wang, W.J.Zhu, X.Guo, T.P.Ma, J.B.Tucker and M.V.Rao, IEEE IEDM 99 Technical Digest 1999; p.209.

4. J.B.Tucker, S.Mitra, N.Papanicolaou, A.Siripuram, M.V.Rao and O.W.Holland, Diamond and Related Materials 11, 392 (2002).

5. J.B.Tucker, N.Papanicolaou, M.V.Rao, and O.W.Holland, Diamond and Related Materials 11, 1344 (2002).

6. J.B.Tucker, M.V.Rao, N.Papanicolaou, N.Mittereder, J.Ellaser, B.Clock and O.W.Holland, IEEE Transactions on Electron Dev. 48, 2665 (2001).

7. S. Mitra, M. V. Rao, N. Papanicolaou, K. A. Jones, M. Derenge, O. W. Holland, R. D. Vispute, and S. R. Wilson, Journal of Applied Physics. 95 , 69 (2004)

8. S. Mitra, M. V. Rao, K. Jones, N. Papanicolaou, and S. Wilson, Solid-State Electronics.47, 193(2003).

9. S. Mitra, M. V. Rao, and K. A. Jones, Solid-State Electronics.48, 143(2004).

GENERAL INSTRUCTIONS FOR COMPLETING SF 298

The Report Documentation Page (RDP) is used for announcing and cataloging reports. It is important that this information be consistent with the rest of the report, particularly the cover and title page. Instructions for filling in each block of the form follow. It is important to **stay within the lines** to meet **optical scanning requirements.**

Block 1. Agency Use Only (Leave blank)

Block 2. Report Date. Full publication date including day, month, and year, if available (e.g. 1 Jan 88). Must cite at least year.

Block 3. Type of Report and Dates Covered. State whether report is interim, final, etc. If applicable enter inclusive report dates (e.g. 10 Jun 87 - 30 Jun 88).

Block 4. Title and Subtitle. A title is taken from the part of the report that provides the most meaningful and complete information. When a report is prepared in more than one volume, repeat the primary title, and volume number, and include subtitle for the specific volume. On classified documents enter the title classification in parentheses.

Block 5. Funding Numbers. To include contract and grant numbers; may include program element number(s) project number(s), task number(s), and work unit number(s). Use the following labels:

```
C  - Contract      PR - Project
G  - Grant         TA - Task
PE - Program       WU - Work Unit
     Element            Accession No.
```

Block 6. Author(s). Name(s) of person(s) responsible for writing the report, performing the research, or credited with the content of the report. If editor or compiler, this should follow the name(s).

Block 7. Performing Organization Name(s) and Address(es). Self-explanatory.

Block 8. Performing Organization Report Number. Enter the unique alphanumeric report number(s) assigned by the organization performing the report.

Block 9. Sponsoring/Monitoring Agency Name(s) and Address(es) Self-explanatory.

Block 10. Sponsoring/Monitoring Agency Report Number. (*if known*)

Block 11. Supplementary Notes. Enter information not included elsewhere such as; prepared in cooperation with....; Trans. of...; To be published in.... When a report is revised, include a statement whether the new report supersedes or supplements the older report.

Block 12a. Distribution/Availability Statement. Denotes public availability or limitations. Cite any availability to the public. Enter additional limitations or special markings in all capitals (e.g. NORFORN, REL, ITAR).

```
DOD   - See DoDD 4230.25, "Distribution
          Statements on Technical
          Documents."
DOE   - See authorities.
NASA  - See Handbook NHB 2200.2.
NTIS  - Leave blank.
```

Block 12b. Distribution Code.

```
DOD   - Leave Blank
DOE   - Enter DOE distribution categories
          from the Standard Distribution for
          unclassified Scientific and Technical
          Reports
NASA  - Leave Blank.
NTIS  - Leave Blank.
```

Block 13. Abstract. Include a brief (*Maximum 200 words*) factual summary of the most significant information contained in the report.

Block 14. Subject Terms. Keywords or phrases identifying major subject in the report.

Block 15. Number of Pages. Enter the total number of pages.

Block 16. Price Code. Enter appropriate price code (NTIS *only*).

Block 17. - 19. Security Classifications. Self-explanatory. Enter U.S. Security Regulations (i.e., UNCLASSIFIED). If form contains classified information, stamp classification on the top and bottom of the page.

Block 20. Limitation of Abstract. This block must be completed to assign a limitation to the abstract. Enter either UL (Unlimited) or SAR (same as report). An entry in this block is necessary if the abstract is to be limited. If blank, the abstract is assumed to be unlimited.